

5

10

**DATA SERVICE COMMUNICAITON SYSTEM AND
METHOD FOR MAKING DATA SERVICE THEREIN**

15
20
25
30
35
40
45
50
55
60
65
70
75
80
85
90
95
100

BACKGROUND OF THE INVENTION

Field of the Invention

The present invention relates to a data service communication system, and a method for making a data service in the communication system.

5 Background of the Invention

10 In general, a reduction of communication system load and an enhancement of a data transmission rate between mobile stations are absolutely required when a data service is made between the mobile stations. Keeping pace with a sharp increase of demand for mobile stations, identical to the speech communication, necessity for a radio communication that requires securing a mobility of communication terminals is increasing even for the data communication. Traditionally, the radio data service has been used for a file transmission. Recently, other than the file transmission, there are information search at access to a computer, an Internet access, an industry computer access, and facsimile transmission and reception in the radio data service. In other words, the radio data service is, in a general term, inclusive of all services that can be implemented by radio among the services available from current PSTN (Public Switched Telephone Network) and PSDN (Public Switched Data Network). Therefore, the radio data service is inclusive of various applications, such as a report transmission from a site to a main office of information media, e-mail transmission and reception, a report transmission to a main office by an employee on outside duty, and the like.

20 The radio service has been made available by adding an IWF (Inter-Working Function) to a lower structure of a current speech communication network. That is, the IWF made the radio data communication available. The mobile communication system includes elements each having an access function, such as a frame relay and X.25/PRI (Primary Rate Interface), for making access to other communication network. In other words, the mobile

communication system provides users with data services, such as circuit data services and packet data services linked with other communication network, such as the PSTN, Internet, and PSPDN (Packet Switched Public Data Network). The standards for the radio data service includes IS-99, IS-707, IS-657, and IS-658, which are suggestions by the EIA (Electronic Industry Association) /TIA (Telecommunication Industry Association). According to the suggestions, the radio data service has operational functions, maintenance functions, and statistical functions separate from an MSC (Mobile Switching Center), operative independent from the MSC. FIG. 1 illustrates a diagram showing traffic paths used for carrying out data service in a related art mobile communication system.

Referring to FIG. 1, service options defined for providing the radio data service in a related art CDMA (Code Division Multiplication Access) mobile communication system includes a circuit data service option and a packet data service option.

First, the circuit data service option includes an 8K asynchronous data service (0x0004), an 8K G3 facsimile data service (0x0005), a 13K asynchronous data service (0x000C), a 13K G3 facsimile data service (0x000D), an 8K asynchronous renewal data service (0x1004), and a 13K G3 facsimile renewal data service (0x1005).

Second, the packet data service option includes a 13K PPP (Point to Point Protocol) packet data service (0x000F), a 13K CDPD (Cellular Digital Packet Data) packet data service (0x0010), an 8K PPP renewal packet data service (0x1007), an 8K CDPD renewal packet data service (0x1008), and a fast packet data bearer service (0x0016 ~ 0x0019).

As described, for carrying out a data service by taking one of the defined service options, the mobile communication system is required to set up a call via the IWF 109 in FIG. 1 and a PDSN functional entity, and a data traffic path through the call. Such a related art method for carrying out a radio data service will be explained in detail with reference to a

protocol stack in FIG. 2. FIG. 2 illustrates a protocol stack showing a related art method for carrying out a radio data service. As described, for carrying out a data service in a related art mobile communication service, the protocol stack in FIG. 2 is required to be observed, for which the IWF is required. That is, when there are mobile stations 101 and 103 requiring calls according to one of the data service options defined in the related art mobile communication system, the IWF 109 is known this fact. Then, a data traffic path is set up between the mobile stations 102 and 103 and the IWF 109. In detail, when the mobile station 102 in FIG. 1 requests a call according to the service option defined in advance for a data service, the mobile station 102 and a first base station 104 come into a traffic state. Then, as shown in FIG. 2, the mobile station 102 and the base station 104 set up a RLP (Radio Link Protocol), and set up a PPP protocol to the IWF 109 via the MSC 108. In this instance, as shown in FIG. 2, a relay layer is set up between an SDU (Service Data Unit) in the base station 104 and the MSC 108, and the MSC 108 and the IWF 109, respectively. An ISLP (Inter-System Link Protocol) of the IS-658 is used in a relay layer section. As described, according to the related art, the data service can be carried out between mobile stations in the same network, between stationary stations in the same network, and between a mobile station in a first network and a stationary station in a second network. All the foregoing data services are required to set up a data traffic path between the mobile or stationary station and the IWF, without fail.

The problems in the related art will be discussed.

First, since the IWF is invariably required even if a data service is carried out between mobile stations belonging to the same network, it is required in data service to proceed data division process in duplication in data transmission, which increases a load on the communication system.

Second, the invariable setting up of a traffic path via the IWF even in a case the data service is carried out between mobile stations within the same network requires much time in data transmission and reception.

SUMMARY OF THE INVENTION

Accordingly, the present invention is directed to a data service communication system, and a method for making a data service in the communication system that substantially obviates one or more of the problems due to limitations and disadvantages of the related art.

An object of the present invention is to provide a data service communication system, and a method for making a data service in the communication system, which can reduce a system load when the data service is made between mobile stations within the same network.

Another object of the present invention is to provide a data service communication system, and a method for making a data service in the communication system, which can reduce data transmission and reception time periods when the data service is made between mobile stations within the same network.

Additional features and advantages of the invention will be set forth in the description which follows, and in part will be apparent from the description, or may be learned by practice of the invention. The objectives and other advantages of the invention will be realized and attained by the structure particularly pointed out in the written description and claims hereof as well as the appended drawings.

To achieve these and other advantages and in accordance with the purpose of the present invention, as embodied and broadly described, a particular service option is defined in advance for a data service between mobile stations within the same network.

According to another aspect of the present invention, a speech traffic path is set up between an origination mobile station and a destination mobile station through the MSC by a

VCE in a base station controller for carrying out the data service without the IWF within the same network.

According to further aspect of the present invention, the MSC switches the speech traffic path to the data traffic path in interlock with a BSP, a CCP, and an SBP in the base station controller.

According to the foregoing aspects of the present invention, when the origination mobile station request the data service according to the particular service option, the speech traffic path is set up between the origination mobile station and the MSC by a VCE in the base station controller. The MSC senses the particular service option and switches the speech traffic path to the destination mobile station. The data service is carried out between the origination mobile station and the destination mobile station through the set up speech traffic path.

It is to be understood that both the foregoing general description and the following detailed description are exemplary and explanatory and are intended to provide further explanation of the invention as claimed.

BRIEF DESCRIPTION OF THE DRAWINGS

The accompanying drawings, which are included to provide a further understanding of the invention and are incorporated in and constitute a part of this specification, illustrate embodiments of the invention and together with the description serve to explain the principles of the invention:

In the drawings:

FIG. 1 illustrates a diagram showing a related art communication system and traffic paths for carrying out data service;

FIG. 2 illustrates a diagram showing a protocol stack of a related art communication

system for carrying out a data service;

FIG. 3 illustrates a diagram showing a communication system and traffic paths for carrying out a data service in accordance with a first preferred embodiment of the present invention;

5 FIG. 4 illustrates a diagram showing a communication system and traffic paths for carrying out a data service in accordance with a second preferred embodiment of the present invention; and,

FIG. 5 illustrates a diagram showing a process for carrying out a data service in a communication system of the present invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

10 Reference will now be made in detail to the preferred embodiments of the present invention, examples of which are illustrated in the accompanying drawings. The present invention suggests no use of an IWF when a data service is made between mobile stations within the same network. Therefore, observation of a protocol stack related to a network in
15 a currently defined protocol stack for a data service is not required. FIG. 3 illustrates a diagram showing a communication system and traffic paths for carrying out a data service in accordance with a first preferred embodiment of the present invention.

Referring to FIG. 3, in the communication system in FIG. 3, a first base station 304 to which a first mobile station 302, an origination side, belongs and a second base station 305 to
20 which a second mobile station 303, a destination side, belongs use a first base station controller 306 and a second base station controller 307, respectively. In other words, the first base station 304 and the second base station 305 use base station controllers different from each other. In FIG. 3, the terminals 300 and 301 represent computers, to which the first mobile station 302 and the second mobile station 303 are connected respectively for data

service. Meanwhile, a particular service option is defined in advance between the mobile stations 302 and 303 for carrying out the data service. For an example, when the first mobile station 302 requests the second mobile station 303, an origination side, for a call to request the data service according to a particular service option defined in advance, a system, i.e., an MSC 308 attempts to connect the call requested by the first mobile station 302, the origination side, to the second mobile station 303, not through an IWF 309, but directly. In this instance, the MSC 308 sets up a data traffic path between the first mobile station 302, the origination side, and the second mobile station 303, the destination side, in interlock with BSP (signaling processor of Base Transceiver Station), CCP (Call Control Processor), and SBP (Selector/Vocoder Bank Processor), sub-systems of the base station controller 306 for the first mobile station 302 and the base station controller 307 for the second mobile station 303. In this instance, the MSC 308 sets up the call such that a general speech traffic path is used as a data traffic path.

FIG. 4 illustrates a diagram showing a communication system and traffic paths for carrying out a data service in accordance with a second preferred embodiment of the present invention, wherein, different from the first preferred embodiment, base stations 404 and 405 use the same base station controller 406. The reference numerals 400 and 401 represent computers, the same as the first embodiment, connected to respective mobile stations, for making the data service.

When the first mobile station 403 request the second mobile station 403 for a call, an RLP (Radio Link Protocol) is set up between the first base station 404, the base station controller 406, the MSC 408, and the first mobile station 402. In other words, the RLP is set up between a VCE (Voice Channel Element) in the base station controller 406 and the first mobile station 402. Then, the MSC 408 informs the second mobile station that the call is

requested by the first mobile station 402 by, upon sensing a particular service option defined in advance, switching a speech traffic path, not to an IWF, but to the second mobile station, a destination side mobile station, and paging the second mobile station. Upon reception of a response to the paging from the second mobile station according to the same particular service option, the MSC 408 connects the first mobile station 402 to the second mobile station 403 through the switched speech traffic path. The first mobile station 402 and the second mobile station 403 carries out the data service through the switched traffic service. As explained, according to particular service options defined in advance between mobile stations within the same network, the base stations carries out a data service function, and the MSC directly switches the general speech traffic path without passing through the IWF, to set up a data traffic path between the mobile stations. In other words, in the present invention, the IWF 410 serves nothing in carrying out the data service within the same network.

FIG. 5 illustrates a diagram showing a process for carrying out a data service in a communication system of the present invention.

Referring to FIG. 5, a first mobile station requests a second mobile station for a data service taking a particular service option defined in advance. (S500). The particular service option is an option for the data service defined in advance between the first and second mobile stations. Then, the MSC checks whether the call requested by the first mobile station is according to a particular service option. (S501). If the requested call is found to be the particular service option as a result of the check, the MSC does not transfers the requested call to the IWF, but handles in a fashion identical to a speech call even if the requested call is a call for a data service (S502), i.e., the MSC switches the speech traffic path to the second mobile station instead of the IWF. Then, when the first mobile station is in a traffic state, an SDU (Service Data Unit) in the base station and a VCE in the base station controller set up a

RLP to the first mobile station (S503). Then, the MSC requests the second mobile station for a paging (S504). When the second mobile station makes a response to the paging according to the particular service option, even if the requested call is a call requesting for the data service, the MSC does not transfer the set up of the requested call to the IWF, but handles the requested call identical to a general speech call (S505). When the second mobile station is in a traffic state, the SDU in the base station and the VCE in the base station controller set up the RLP to the second mobile station (S506). When the second mobile station makes a response to the paging, the MSC switches the data traffic path from the first mobile station to the second mobile station, to set up the call for the data service (S507). Then, the first mobile station sets up a PPP to the second mobile station through the data traffic path set up between the first mobile station and the second mobile station (S508). Once set up of the PPP is completed, the data service can be made between the first mobile station and the second mobile station. That is, data transmission and reception between the mobile stations can be made (S509).

As has been explained, the data service communication system, and the method for making a data service in the communication system have the following advantages.

First, the IWF can be dispensed with when a data service is carried out between mobile stations within the same network, which prevents dividing a data in duplication, that reduces a load of the system, i.e., the MSC.

Second, the direct data transmission and reception without passing through the IWF when the data service is carried out between mobile stations in the same network permits a fast data service.

Third, no traffic path is required to be set up to the IWF when the data service is carried out between mobile stations in the same network, which allows an effective utilization

of system resources. For an example, more system resource can be allocated to the mobile stations accessed, not to the same network, but to different networks, and requested services.

Fourth, a variety of data services are made available without the IWF within the same network.

5 It will be apparent to those skilled in the art that various modifications and variations can be made in the data service communication system, and the method for making a data service in the communication system of the present invention without departing from the spirit or scope of the invention. Thus, it is intended that the present invention cover the modifications and variations of this invention provided they come within the scope of the appended claims and their equivalents.

10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000